Rigid productivity by design

Océ Arizona 6100-Series

you can

| UP TO 155M ² PER HOUR |
|--|
| TRUE FLATBED ARCHITECTURE |
| VERSATILE RIGID MEDIA APPLICATIONS |
| OCÉ VARIADOT™ IMAGING TECHNOLOGY FOR SUPERIOR PRINT QUALITY |
| AUTOMATED PRINTHEAD MAINTENANCE SYSTEM |
| PNEUMATIC MEDIA REGISTRATION PINS |
| HIGH-FLOW VACUUM SYSTEM |
| NON-STOP PRINTING |

An easy-to-use high volume flatbed, the Océ Arizona 6100 Series delivers highly productive rigid media printing and sets new standards for print quality, application versatility and reliability.



The single best option

Purpose designed for graphics professionals and built without compromise, Océ Arizona 6100 Series dedicated high volume flatbed systems are ideal for sign and display graphics print service providers with a production potential in excess of 30,000m² per year.

Next-level productivity

Designed as a productivity platform, the Océ Arizona 6100 Series delivers fast, reliable and high quality prints at speeds of up to 155m² per hour. An extra-large, dual origin flatbed table with two independent vacuum zones allows for non-stop production of standard size 1.25 x 2.5 m boards with simultaneous printing and media loading/unloading.

Exceptional print quality

A new 6-colour Océ VariaDot[™] imaging technology produces ink droplets from 6 to 42 picolitres resulting in superb image detail, smooth colour transitions and vivid, uniform solid colours. Light Cyan and Light Magenta are used for reliable printing at production print speeds, and improve the smoothness of quarter tone colours, like skin tones.

The print sharpness and print geometry over the entire flatbed is further enhanced by actively mapping the table and adjusting the pixel placement, called Active Pixel Placement Compensation.

Rigid media application versatility

A dedicated, true flatbed system, the Océ Arizona 6100 Series opens up a wealth of production possibilities. An extra-large 2.5 x 3.05 m vacuum table, designed to keep media and objects stationary during printing, offers optimal print quality and unrivalled versatility. It supports the broadest range of rigid media applications including: printing on odd shaped, heavy, smooth or pre-cut rigid media; high value multi-layer applications; double-sided prints; large tiled prints over multiple boards; and edge-to-edge prints – all in perfect register and geometry and without hassle or mess.

The Océ Arizona 6160 XTS can easily be upgraded at any time to an Océ Arizona 6170 XTS by adding an additional ink channel for white ink support. An API (application programming interface) allows for easy integration with third-party automation systems for instance for automated media load/unload systems.

Unmatched reliability and ease-of-use

Pneumatic registration pins ensure quick, repeatable, easy loading of rigid media in perfect register every time. Combined with a high-flow vacuum system for effective pull-down of even warped rigid media, it takes only seconds to load the largest boards.

An innovative Automated Printhead Maintenance System provides completely hands-free printhead cleaning in less than 25 seconds per colour, ensuring consistent nozzle performance print after print.



Specifications: Océ Arizona 6100-Series

| | Océ Arizona 6160 XTS | Océ Arizona 6170 XTS | |
|--|--|---|--|
| PRINTER | | | |
| Machine type | High-volume UV Flatbed printer | | |
| Printing method | Piezoele | ctric inkjet | |
| Number of nozzles | 6 x 636 nozzle printheads per channel, 6 colour channels, 22,896 nozzles in total | 6 x 636 nozzle printheads per channel, 7 colour channels, 26,712 nozzles in total | |
| Image technology | Océ VariaDot [®] grayscale imaging technology | | |
| Print resolution | | | |
| PRINT MODES - MAX M ² /HR Express 155 Production 100 Quality 72 | | | |
| | | | |
| | | | |
| INK SYSTEM | | | |
| Colours | Océ IJC261 UV curable inks: Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta in 3 litre, quick-exchange pouches | Océ IJC261 UV curable inks: Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta in 3 litre, quick-exchange pouches White in a 2 litre, quick-exchange pouch | |
| SYSTEM DESIGN | | | |
| True Flatbed | True flatbed architecture designed and build for optimised printing on rigid or sheet media or objects | | |
| Media size | 2.50 m x 3.05 m x 50.8 mm | | |
| Print area | 2.51 m x 3.06 m, edge-to-edge printing (full bleed) | | |
| GEOMETRIC ACCURACY | | | |
| Line width | ±0.8 mm max error, measured over 2.5 m | | |
| Line length | ±1.0 mm max error, measured over 3.05 m | | |
| Line straightness/width | 0.7 mm max error, measured over 2.5 m | | |
| Line straightness/length | 0.7 mm max error, measured over 3.05 m | | |
| Diagonal Error | 1.0 mm max error, measured over 3.05 m x 2.5 m | | |
| INTERFACE & SOFTWARE | | | |
| Interface type | 10/100/1000Base-T | | |
| Production Management Software | TBD | | |
| Image Processing Software | ONYX® Thrive™ v11.1 or greater | | |
| OPERATING ENVIRONMENT | | | |
| Electrical | Three-phase, 200-240 VAC 50/60Hz 30A (Delta) OR Three-phase, 347-415 VAC 50/60Hz 20A (Wye) | | |
| Continuous Power Consumption | 9.6 kW (max) | | |
| Compressed Air (supplied by customer) | y customer) Customer must provide pressure-regulated, clean, dry air by use of: Coalescing filter Air regulator (set to 105 psi / 723 kPa) Vianch OD air tubing – connects air regulator to printer Flow requirements: Pressure (max): 120 psi / 827 kPa Peak flow: 340 I/m at 100 psi / 690 kPa Continuous flow: 28//m at 100 psi / 690 kPa | | |
| | | | |
| | | | |
| | | | |
| Temperature | 18° to 30° C | | |
| Relative humidity | 30-70%, non-condensing (certain media may require a smaller RH operating range) | | |
| Room Ventilation | TBC | | |
| Operating Altitude | 2000 m | | |
| Dimensions (printer only) | 5.72 x 4.82 m | | |
| Table height range (Min/Max) | 0.895 to 0.915 m | | |
| | | | |
| Overall height | | 1.48 m | |
| Weight (printer only) | 1,815 kg | | |
| CONSUMABLES | | | |
| mediaguide.oce.com | Visit our online guide to find the right media for your printer and application, including matching Océ color profiles | | |
| OPTIONS & UPGRADE PATH | | | |
| Options | Colour Channel Upgrade - Add colour channel functionality to the printer at any time | None | |
| Upgrade path | Field upgradeable to an Océ Arizona 6170 XTS model configuration - Adds White ink functionality for transparent, backlit and non-white media applications | None | |

Océ Arizona is a registered trademark of Océ Display Graphics Systems Océ VariaDot is a registered trademark of Océ Technologies B.V. ONYX is a registered trademark, and ONYX Thrive is a trademark, of ONYX Graphics, Inc.

Canon Inc.

canon.com Canon Europe

3 The Square, Stockley Park Uxbridge, Middlesex UB11 1ET United Kingdom

Canon Europe Ltd

canon-europe.com English Edition © Canon Europa N.V., 2014

